

Family: EDGEBANDING MACHINES	Code: 004686
SubFamily: Double Sided Edgebanders And Combination Edgebanding Machines	
Brand: HOMAG	
Model: KL 26/05/A12/25	



Type of edging	Thin edge Thick edge
Gluing System	EVA Hotmelt
Trimming Unit	yes
Combination Squaring Edgebanding Machine	First and Second Pass
Operating Units Right Side	5 nr
Operating Units Left Side	5 nr
Max. panel height	60 mm
Min. edge thickness	0.4 mm
Max. edge thickness	12 mm
Conveyor Track with dogs	yes
Distance between dogs	1000 mm
Top pressure	yes

Pressure with	rubber belt
Panel support guides	yes
Same technical characteristics on the left side	yes
Edge coil magazine	yes
no. positions	1
Gluing system	yes
glue pot for EVA hot melt glue	yes
premelter for EVA hot melt glue	yes
Roller set to press the edge	yes
no. pressure roller	7
No. Edge Processing Units	5
NO. EDGE PROCESSING UNITS 1 Processing Unit : end trimming no. motors : 2 motor power : 0.8 KW r.p.m. : 12000 RPM	
NO. EDGE PROCESSING UNITS 2 Processing Unit : top and bottom rough trimming no. motors : 2 motor power : 1.5 KW r.p.m. : 12000 RPM	
NO. EDGE PROCESSING UNITS 3 Processing Unit : fine trimming to trim and round no. motors : 2 motor power : 0.5 KW r.p.m. : 12000 RPM	
NO. EDGE PROCESSING UNITS 4 Processing Unit : edge scraping	
NO. EDGE PROCESSING UNITS 5 Processing Unit : buffing no. motors : 2	
Units fitted on overtables	yes

Control system NC 21

Safety standard CE mark yes
