

Family: EDGEBANDING MACHINES	Code: 004516
SubFamily: Double Sided Edgebanders And Combination Edgebanding Machines	
Brand: HOMAG	
Model: KAL 526/6/A3/30/S2	



Type of edging	Thin edge Thick edge
Gluing System	EVA Hotmelt
Premilling Unit	yes
Trimming Unit	yes
Combination Squaring Edgebanding Machine	First and Second Pass
Max Panel Width	118.11 inch
Max feed speed	131.23 ft/min
Operating Units Right Side	6 nr
Operating Units Left Side	6 nr
Min. panel height	.39 inch
Max. panel height	2.36 inch
Max. panel width	118.11 inch

Min. edge thickness	.02 inch
Max. edge thickness	.12 inch
Max. forward feed speed	131.23 ft/min
Conveyor Track with dogs	yes
Distance between dogs	39.37 inch
Top pressure	yes
Pressure with	rubber belt
Panel support guides	yes
Infeed panel alignment system	yes
No. Panel Sizing / Milling units Left Side	1

NO. PANEL SIZING / MILLING UNITS LEFT SIDE 1

Unit : pre-milling unit

automatic timed intervention : yes

Same technical characteristics on the left side	yes
Edge coil magazine	yes
no. positions	2
Gluing system	yes
glue pot for EVA hot melt glue	yes
premelter for EVA hot melt glue	yes
Roller set to press the edge	yes
no. pressure roller	5
No. Edge Processing Units	4

NO. EDGE PROCESSING UNITS 1

Processing Unit : end trimming
no. motors : 2

NO. EDGE PROCESSING UNITS 2

Processing Unit : top and bottom rough trimming
no. motors : 2

NO. EDGE PROCESSING UNITS 3

Processing Unit : fine trimming to trim and round
no. motors : 2

NO. EDGE PROCESSING UNITS 4

Processing Unit : buffing
no. motors : 2

Units fitted on overtables	yes
Control system	POWER CONTROL PC 22
Safety standard CE mark	yes