



FASTENING SCREW M16

	2810	6018	9225	
2810	3207.5	3207.	5 1425	_
500	-	500	500	
670 570			020	
4525		\$ 258	A 1500	

TECHNICAL DATA			
TOTAL DUST EXTRACTION CAPACITY CA. M3/H		22800	
AIR VELOCITY M/SEC		28	
COMPRESSED AIR CONSUMPTION APPROX. SL/MIN		2060	
NEGATIVE AIR PRESSURE IN MM/WS		200	
TOTAL CONNECTED LOAD CA. KW 87			
NOMINAL CURRENT APPROX. A 1		148	
RECOMMENDED BACK-UP FUSE A		200	
ELECTRICA GOUNDING POINT - MACRINE PRINCIPON MOT GRAMARITED MINDLE TIPROST GOUNDING IN A CORDINARY UNIT LOCAL ELECTRICA, LODG EARTHING RESTANCE - QI PROTECTIVE GECULTS OUT FRAMISSIES IN COMBINATION WITH AN ALL COMBINET SENSITIVE PROFILES IN COMBINATION WITH AN ALL COMBINET SENSITIVE - QIANTING THE SWITCH AN ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - CONTROL OF THE SWITCH AND ALL COMBINET SENSITIVE - QUESTION - COMBINET -			
OUTER EDGE OF CHAIN TRACK RESP. FIXED EDGE WORKPIECE OVERHANG 0			
CONNECTION FOR COMPRESSED AR WITH HOSE SH' INSIDE DUANETER ISMM SUPPLYCT SUPPLYCT STANDAGE COMPRESSED AR QUALITY ACCROMING TO SEG 573-1 QUALITY CLASS SUD MINISTREE CLASS WATER CONTENT CLASS 4 TOTAL OL. CONTINT CLASS 4 TOTAL OL. CONTINT CLASS 3			



003873
DOUBLE SIDE SQUARING EDGE BANDER
HOMAG
05.12.2018