



CONNECTING CABLES, SWITCH CABINET - MACHINE LAYING ON THE FLOOR. CABLES MUST BE PROVIDED IN CLOSED CABLE CHANNELS ACCORDING TO REGULATIONS (ON SITE)

THE SUCTION HOSE MUST BE MADE OF LIGHT-NEUTRAL MATERIAL, BECAUSE THE SPRAY LIGHT CAN CAUSE FUNCTIONAL FAILURES OF THE SPARK SENSOR

WORKING HEIGHT: 950 mm

TECHNICAL DATA	
TOTAL SUCTION CONSUMPTION C.A. M3/H	4580
AIR CONSUMPTION C.A. NL/MIN	900
PRESSURE LOSS C.A. PA	2500
TOTAL INSTALLED POWER C.A. KW	27
NOMINAL CURENT C.A. A	49
BACKUP FUSE A	63

Disegnatore: Ferwood spa

Titolo: 005074\_MA

Descrizione: Single sided Edgebander HOMAG KAL 310/7/A3

**FerWood®**  
BRILLIANT SOLUTIONS FOR WOOD

FerWood srl - Via Langhe 4/A 1204<sup>o</sup> Pollenzo (CN) Italy  
Tel: +39 0172 474073 - fax: +39 0172 471442

email: info@ferwoodgroup.com

Sistema:

Foglio: A3

Tutti i diritti sono riservati da Copyright vietata la riproduzione All rights reserved by Copyright is forbidden to reproduce