



PRESENZA CAPPE
HOTTES EXISTANTES
EXISTING HOODS
ANWESENDE STUTZE

	SI OU YES JA	Ø	INTERASSE ENTRE-AXES CENTER DISTANCE SWISOHENABSTAND	
A	SI	195	585	
B	SI	160	414	
C	SI	160	371	
D	SI	160	618	
E	SI	160	~876	
F	SI	195	393	
G	SI	195	410	
H	SI	195	376	
I	SI	195	596	
L	SI	160		
W	SI	150		

TECHNICAL DATA CAN BE CHANGED.
LES DONNEES TECHNIQUES PEUVENT MODIFIEES.
DIE TECHNISCHEN DATEN KÖNNEN GEÄNDERT WERDEN.
I DATI TECNICI NON SONO IMPEGNATIVI E POSSONO ESSERE MODIFICATI

QUADRO ELETTRICO
CADRE ELECTRIQUE
ELECTRIC PANEL
ELEKTRISCHE SCHALT TAFEL

ASPIRAZIONE
ASPIRATION
SUCTION
ANSAUGUNG

ALIMENTAZIONE PNEUMATICA
ALIM. PNEUMATIQUE
PNEUMATIC FEEDING
PNEUMATISCHE VERSORGUNG

ALIMENTAZIONE ELETTRICA
ALIM. ELECTRIQUE
ELECTRIC FEEDING
ELEKTRISCHE VERSORGUNG

FerWood
BRILLIANT SOLUTIONS FOR WOOD

LAY-OUT: LNC USK 1350 -I M4 + USK 1350 M4
SA-005864_SA-005865

N° DI CODICE :
09/589006/30

SCALA:
1 : 50

DATA:

FIRMA:
F | |