



Pressengewicht ca. 35.000 kg
 Fundamentbelastung ca. 10 N/cm²
 press weight appr. 35.000 kg
 foundation load appr. 10 N/cm²

All cable channels are local supply

vertical junction canal

All cable trays made of metal.

Foundation load
 for the whole floor
 Foundation load 2 N/cm²
 point load/lumped load 8t

The fixation of the cables in the cable platforms or cable routes has to be provided by the customer at site. (e.g. cable fixings)

max. tolerances for
 press foundation +/- 1 mm

Please make sure that no flexible fixtures such as chains or ropes are used for fixing the cable links.

All foundation, bricklaying, lag bolts fixing and implemets etc. also cable ducts and its covering are LOCAL SUPPLY

A fix fastening is absolutely necessary.

The buyer is responsible for securing all walkways and hazardous areas of the line by means of safeguards or safety covers. These safety devices must be constructed in compliance with local regulations and standards.

Alle Überänge bzw. Gefahrenbereiche der Anlage sind "bauseits" durch Unwehungen oder Abdeckungen zu sichern. Bei der Ausführung sind örtlichen Sicherheitsvorschriften und Normen zu beachten.

Disegnatore: Ferwood srl	
Titolo: 004781	
Descrizione: Membrane Press WEMHOENER Variopress Professional 3000	
Data:	Sistema:
Foglio: A3	

FerWood®
 BRILLIANT SOLUTIONS FOR WOOD
 FerWood srl - Via Langhe 4/A 12042 Pollenzo (CN) Italy
 Tel: +39 0172 474073 - fax: +39 0172 471442
 email: info@ferwoodgroup.com

Tutti i diritti sono riservati da Copyright vietata la riproduzione All rights reserved by Copyright is forbidden to reproduce