


WORKPIECE SIZES			
LENGTH MIN./MAX.		200 MM / 2500 MM	7,87" / 98,4"
WIDTH MIN./MAX.	IN PROCESSING	70 MM / 1000 MM	2,75" / 39,4"
WIDTH MIN./MAX.	IN THROUGH-FEED	70 MM / 1300 MM	2,75" / 51,2"
THICKNESS MIN./MAX.		4 MM / 80 MM	0,15" / 3,15"

WITHOUT OUR PERMISSION THIS DRAWING MUST NOT BE REPRODUCED NOR DUPLICATED
NOR MADE ACCESSIBLE TO THIRD PARTIES OR COMPETITORS

ELECTRICAL GROUNDING POINT - MACHINE
FUNCTION NOT GUARANTEED WITHOUT PROPER GROUNDING IN ACCORDANCE WITH LOCAL ELECTRICAL CODE.

OUTER EDGE OF CHAIN TRACK RESP. FIXED EDGE WORKPIECE OVERHANG '0'

COMPRESSED AIR CONECTION INNEN- R1/2'
ZULEITUNG R1'
AIR PRESSURE IN SUPPLY LINE MIN. 7 BAR (102 PSI)
STANDARD COMPRESSED AIR QUALITY ACCORDING TO ISO 8573- 1
QUALITY CLASS 4 IN CASE OF WATER CONTENT
QUALITY CLASS 3 IN CASE OF TOTAL OIL CONTENT AND SOLID IMPURITIES

FOR THE ROOM CONDITIONS DURING MACHINE OPERATION PLEASE SEE OUR SAFETY REGULATIONS

SUBJECT TO CHANGE

WEEKE

OPTIMAT BHX 500
0-250-12-2586

FerWood®
BRILLIANT SOLUTIONS FOR WOOD

PROJECT:	
CODE:	004458
TYPE:	CNC WORKING CENTER
BRAND:	WEEKE BHX 500
DESIGNER:	
DATE:	
FILE:	