



TYP HPP250/38/38

MAXIMUM PANEL SIZE	MM (INCH)	3800 X 3800 (149,61" X 149,61")
MINIMUM PANEL SIZE	MM (INCH)	50 X 50 (1,97" X 1,97")
SAW BLADE PROJECTION	MM (INCH)	75 (2,95")
CUTTING LENGTH	MM (INCH)	3800 (149,61")

07/04/2025

"HOMAG non si assume alcuna responsabilità circa la corrispondenza della composizione attuale della macchina rispetto alla descrizione del layout"

Pas s m a B		Ad m a B
TECHNICAL DATA		
TOTAL DUST EXTRACTION CAPACITY	M3/H (CFM)	3800 (2236)
AIR VELOCITY	M/SEK (FEET/SEK)	26 (85,28)
COMPRESSED AIR CONSUMPTION	NL/MIN (CFM)	150 (5,25)
DRUCKVERLUST	PA N/M2 (INCH WS)	1200 (4,82)
MAIN SAW MOTOR	KW	7,5 9,2
TOTAL CONNECTED LOAD	KW	12,4 14,1
NOMINAL CURRENT	A	28,25 30,25
RECOMMENDED PREFUSE PROTECTION	A	32 40
LOAD APPROX 1.5N/MM2 CONCRETE QUALITY C25/30 XC1 CAPABLE OF BEARING PRESSURE AND TENSION THICKNESS OF CONCRETE MIN. 200 MM EVENNESS OF FLOOR TOLERANCE $\pm \pm 10 \text{MM}$ ($\pm 0,39"$)		
GROUTING BY CUSTOMER OF THE MOUNTING PLATES WITH CASTING COMPOUND RESISTANT TO SHRINKING AFTER INSTALLATION		
REPRESENTATION AND DIMENSIONING OF INSTALLATIONS PROVIDED BY THE CUSTOMER AND MACHINES OF FOREIGN BRAND WITHOUT GUARANTEE		
WITHOUT THE SAFETY BARRIERS SUPPLIED BY HOLZMA, WHICH ARE SHOWN IN THIS PLAN, THE PRODUCTION EQUIPMENT IS NOT CE-COMPLIANT, AND MUST THEREFORE NOT BE OPERATED.		
ONLY IMMOVABLE WALLS ANCHORED SECURELY TO THE PRODUCTION AREA FLOOR AND THE PRODUCTION AREA ROOF ARE PERMISSIBLE AS AN ACCESS PREVENTION MEASURE AT THE CUSTOMER'S PREMISES.		
	ELECTRICAL GROUNDING POINT - MACHINE FUNCTION NOT GUARANTEED WITHOUT PROPER GROUNDING IN ACCORDANCE WITH LOCAL ELECTRICAL CODE. EARTHING RESISTANCE $< 3 \text{ OHM}$ PROTECTIVE CIRCUIT IS ONLY PERMISSIBLE IN COMBINATION WITH AN ALL-CURRENT-SENSITIVE/SELECTIVE FI-PROTECTIVE SWITCH	
	REFERENCE LINE	
	CONNECTION FOR COMPRESSED AIR WITH HOSE 1/2" (INSIDE DIAMETER 12.7MM) SUPPLY G2" AIR PRESSURE IN SUPPLY LINE MIN. 7 BAR (102 PSI) STANDARD COMPRESSED AIR QUALITY ACCORDING TO ISO 8573-1 QUALITY CLASS SOLID IMPURITIES CLASS 3 WATER CONTENT CLASS 4 TOTAL OIL CONTENT CLASS 3	
	MACHINE ZERO POINT	
	REFERENCE POINT	
PLEASE RETURN THE APPROVED DRAWING IMMEDIATELY, PLEASE GIVE EXACT SIZES OF MODIFICATION		
DATE:	SIGNED:	
DATE:	SIGNATURE OF CUSTOMER	
PLEASE MARK APPLICABLE WITH A CROSS		<input checked="" type="checkbox"/>
CONNECTION CABLE SWITCH CABINET - MACHINE	ON THE FLOOR-BY CUSTOMER	<input type="checkbox"/>
	IN CABLE CHANNEL - BY CUSTOMER	<input type="checkbox"/>
	CIA CEILING MM HIGHT-BY CUSTOMER	<input type="checkbox"/>
Disegnatore: FERWOOD Titolo: LAYOUT Descrizione:		FerWood® BRILLIANT SOLUTIONS FOR WOOD FerWood srl - Via Langhe 4/A 10047 Pollenzo (CN) Italy Tel: +39 0172 474073 - Fax: +39 0172 473442 email: info@ferwoodgroup.com
Data: 1/03/2025	Sistema:	Foglio: A3
Tutti i diritti sono riservati da Copyright vietata la riproduzione All rights reserved by Copyright is forbidden to reproduce.		