



● Electric Power Connection

TECHNICAL DATA

| | | |
|---|---------------------------------------|-------------------------|
| PNEUMATIC | COMPRESSED AIR CONSUMPTION | 390 NL/MIN |
| DUST COLLECTION ATTENTION WEIGHT RELIEF AT EXTRACTION HOSE | EXTRACTION PORT : | |
| | SUCTION CAPACITY | |
| | AIR VELOCITY | |
| | NEGATIVE PRESSURE | |
| ELECTRIC/ELECTRONIC | PROTECTION MODE | IP53 |
| | OPERATING VOLTAGE | 3* 400 VOLT, ±5% |
| | CONTROL VOLTAGE | 24 VOLT |
| | FREQUENCY | 50/60 HZ |
| | NOMINAL CURRENT | 14 |
| | RECOMMENDED PREFUSE PROTECTION | 20 |
| | TOTAL CONNECTED LOAD | 14 |
| THE MACHINE IS NOT DESIGNED FOR A CONNECTION TO A NETWORK WITH FAULT CURRENT PROTECTION SWITCH | | |

Disegnatore: Ferwood srl

Titolo: 005661_MA

Descrizione:
Tilting device for panel
BARGSTEDT P TTL401/12/25

FerWood®
BRILLIANT SOLUTIONS FOR WOOD

FerWood srl - Via Langhe 4/A 12042 Pollenzo (CN) Italy
Tel: +39 0172 474073 - fax: +39 0172 471442

email: info@ferwoodgroup.com

Data: Sistema:

Foglio: A3

Tutti i diritti sono riservati da Copyright[®] vietata la riproduzione All rights reserved by Copyright[®] is forbidden to reproduce