



“HOMAG non si assume alcuna responsabilità circa la corrispondenza della composizione attuale della macchina rispetto alla descrizione del layout”

TYPE

HPP230 38/38

FOR APPROVAL:

DATE: _____ SIGNED: _____

VERIFIED:

DATE: _____ SIGNED: _____

PLEASE RETURN THE APPROVED DRAWING IMMEDIATELY,
OTHERWISE DELIVERY MAY BE DELAYED

SUBJECT TO CONSTRUCTIVE MODIFICATIONS
WITHOUT OUR PERMISSION THIS DRAWING MUST NOT BE
REPRODUCED OR USED BY ANY PARTIES OR COMPETITORS

15926-1

LAWF

19.06.1901

1

MAIN ELECTRICAL CONNECTION

2

SPACE REQUIREMENT
MAINTENANCE

RIGHT

☐ LEFT

3

ROOM FOR SAW BLADE CHANGE

4

PNEUMATIC CONNECTION 1/2"
SUPPLY

X

DUST-COLLECTOR MUFF

5

SAFETY LIGHT BARRIER

CONCRETE QUALITY B25 CAPABLE OF BEARING PRESSURE AND TENSION
THICKNESS OF CONCRETE MIN. 200 MM (7.9")
EVENNESS OF FLOOR: TOLERANCE ± 10 MM (± 0.4 ")

GROUTING BY CUSTOMER OF THE MOUNTING PLATES WITH CASTING COMPOUND
RESISTANT TO SHRINKING AFTER INSTALLATION

REPRESENTATION AND DIMENSIONING OF INSTALLATIONS PROVIDED BY THE CUSTOMER
AND MACHINES OF FOREIGN BRAND WITHOUT GUARANTEE

MAXIMUM PANEL SIZE

3800 x 3800 mm 149.61 x 149.61"

MINIMUM PANEL SIZE

... x ... mm ... x ..."

SAW BLADE PROJECTION

55 mm 2.17"

CUTTING LENGTH RIP SAW

3800 mm 149.61"

CUTTING LENGTH TRIM SAW

... mm ..."

MAIN SAW MOTOR

5.5 KW

TOTAL CONNECTED LOAD

10.2 KW

MAIN SAW MOTOR

7.5 KW

TOTAL CONNECTED LOAD

12.2 KW

AIR PRESSURE REQUIRED *

6 bar 97 psi

TOTAL AIR REQUIREMENTS FOR 10m²/14.5sqm

150 Nm³/min 525 CFM

SUCTION CAPACITY

4400 m³/h 2596 CFM

AIR VELOCITY

26 m/s 85.26 feet/s