

Lift Table

Qty:2

Model: 7P484 Pro-Series

Lift Table Capacity: 4,000 Lbs

Uniformly distributed load

Low Height:

7.50" Vertical Travel: 48.00

Raised Height: 55.50"

Lift Time: 48seconds approx

Note: To accommodate precise matching of the lift table in its fully lowered position with an adjacent object or structure, allow 1/4" additional to the lowered height stated and use shims(shim as per the installation instructions) to match exactly.

Platform Size:

48.00 "Wide x 72.00 " Long

Platform Material:

Smooth Steel Platform

Frame Size:

48" Wide x 64" Long

Install Style:

Stationery - Surface mounted

Finish:

Non-standard paint color - Light, Primed (other than Pentalift Gray) painted to a specific RAL#. Product is primed and painted with Pentalift's standard composition alkyd enamel.

Equipment is mechanically cleaned prior to primer/paint application

Special paints do not have the same composition as standard, and are applied with different equipment. Special paint may not cover as well and may not result in the finish quality desired. Please be aware of this prior to ordering special paint.

Color:

RAL3020 Traffic Red

Primer:

Pentalift Gray

Power Unit:

Self Contained 1HP 115/1/60

Primary Control:

Guarded Foot Pedal Control, constant pressure on 10 feet of cord

This equipment includes Pentalift standard controls and wiring. If there are specific requirements for controls and/or wiring, please ensure these are discussed with your Pentalift representative and confirm that they are listed on quotation before placing order.

Standard Features:

- Straight Toe Guards suitable only for surface mounting, unless accompanied by Toe Sensors
- Highly visible, detailed safety and operation decals for greater visibility and safety
- Lagging brackets welded to frame
- Scissor legs are solid steel, one piece construction with precision reamed holes for accurate alignment and table operation
- Lubricated for life, maintenance free bearings at pivot points
- Pre-wired motor controls (NEMA 12)
- Reservoir is filled with oil
- Exclusive PentaFLOW hydraulic bypass cylinder(s)
- Temporary power wires

Total Weight (lbs): 1,861

Mechanical Options Included

- Toe Guards: Straight Toe Guards

Options Included

- Hydraulic Velocity Fuse: Prevents free fall if the hydraulic hose is severed May not lock with lighter loads
- on platforms
- Maintenance Stand: Maintenance Stand

Electrical Options

- Hydraulic Oil: OIL32 standard lift table

Engineered Items

- Up Travel limit switch set at 40" travel.
- 48" wide frame using longer frame angles. Standard leg and scissor configuration.

Notes & Disclaimers

Customer is responsible for ensuring equipment meets all required codes, regulations, licensing and other applicable items as required